

Estetic[®] Casa Access

- Properties**
- Entry-level product ideal for built-in appliances
 - Thermosetting paint
 - Surface treatment and paint: free of hexavalent chromium and heavy metals

Applications **Entry-level product ideal for built-in appliances (refrigerators, chest freezers, microwave ovens, water heater casings etc)**

Description	Thickness ⁽¹⁾	17 microns
	Composition	Front: 17 microns Back: 5 or 7 microns high-gloss backing coat
	Gloss (Gardner 60°) ⁽¹⁾	Usual: 40-80 GU
	Colours	Specific colours on request
	Appearance	Smooth
	Temporary protection (optional)	Self-adhesive film or heat-sealed film
Performance	Adhesion of the coating (T-bend)	≤ 2 T
	Resistance to cracking on bending (T-bend)	≤ 2 T
	Impact resistance	18 J
	Surface "pencil" hardness	HB to H
	Adherence with no cracks (Erichsen test)	6 mm
	Adhesion on cross-cut	100%
	Salt spray test	192 hours
	Condensation resistance:	
	• QCT test	500 hours
	• Corrosion protection category	CPI2
Compliance with European directives 2002/95/EC and 2011/65/EC on electrical and electronic equipment		ROHS-compliant

Remarks These performance characteristics refer specifically to metallic coating Z100 (guaranteed minimum).
 If any product (film, oil, foam, glue, paint etc) is to be applied after coil delivery, compatibility with the coating needs to be checked first.

(1) Nominal value, tolerance according to EN 10169